



Hydro Guard™ - C1000-MCB Microban® CARBON BLOCK Counter Top Water Filtration System

Hydro Guard™ Total Care Water Systems

are high performance water filtration systems designed to substantially improve the quality of your drinking water. They provide great tasting water while producing water that is cleaner, healthier and safer. We strive to provide top quality products and understand that transforming your water from questionable to premiere quality is really not a matter of chance, it's simply a matter of choice.

Hydro Guard™ Total Care Water Systems

The Hydro Guard™ Total Care Water Filtration Systems are designed to address a broad range of issues relating to your drinking water, including items of health concern that are important to your family's health and wellbeing.

The Hydro Guard™ C1000-MCB incorporates a multi-stage water filtration cartridge designed to provide you with cleaner, clearer, safer, healthier drinking water. One cartridge provides 800 gallons of premium quality drinking water!

Stage 1 –

Hydro Guard's Radial Flow Filtration allows water to enter the cartridge through the radius of the filter. This allows the Stage 1 outer layer to trap and retain larger particles such as dirt, rust and sediment. The FDA CFR 21 compliant fine web polypropylene fibers do not impart color, odor or chemicals into the water and are an ideal pre-filtration media.

Stage 2 –

Water passes through the NSF Certified Coconut Shell Solid Carbon Block filter to reduce items of health concern. The 0.5 micron carbon block pores micro-strain the water to reduce (through mechanical filtration) substances in your water that are 0.5 micron in size or larger. The 0.5 micron pores also aid to increase the systems adsorptive properties. This allows water to have a longer contact time with the carbon wall and permits the efficient reduction of Volatile Organic Compounds (VOC's – Organic Chemicals), PCB, Pesticides, Herbicides, Chloroform and other chlorination by-products.



**Total Care™
Filtration**

HYDRO GUARD™ WATER SCIENCES | PO Box 2235 Chino Hills, CA 91709, USA

Hydro Guard™ - C1000-MCB

Microban® CARBON BLOCK

Counter Top Water Filtration System



The Hydro Guard™ C1000-MCB also incorporates throughout the solid carbon filter Microban® technology. Microban® antimicrobial technology inhibits the growth of bacteria that can cause odors and fouling of the filter surface, so your filter keeps working at peak performance. On an unprotected surface, bacteria can double in number every 20 minutes causing premature fouling of the water filter. Microban® antimicrobial product protection works continuously to inhibit the growth of bacteria that can adversely affect filter performance.

HYDRO GUARD™ End Of Life Indicator (ELI)

The Hydro Guard™ End of Life Indicator (ELI) is another way Hydro Guard™ helps you safeguard your drinking water. The ELI measures time and informs you when it's time to change your filter. This is an added convenience which takes away the guess work and helps ensure your drinking water system is working at optimal performance. Two LED lights update you on the systems operation. The **YELLOW LED** indicates less than 10% of filter capacity remains (*it's time to order a replacement cartridge*), and the **RED LED** indicates the filter capacity has been reached, and it's time to install new cartridge.
Peace of mind made easy!



HYDRO GUARD™ WATER SCIENCES | PO Box 2235 Chino Hills, CA 91709, USA

PRODUCT BENEFITS

- ✓ Excellent Contaminant Reduction **
- ✓ Superior Taste, Odor and Chlorine Reduction**
- ✓ 800 Gallon Capacity**
- ✓ End of Life Indicator (ELI - Filter Change Indicator)
- ✓ VOC Pesticide, Herbicide Reduction**
- ✓ Carbon Block Certified by NSF®
- ✓ Quick & Easy Install
- ✓ Microban® Antimicrobial Protection

PRODUCT SPECIFICATIONS

Rated Capacity:	800 gallons (3028.33 L)
Micron Rating:	0.5µ
Replacement Filter:	HDG-MCB
Flow Rate:	.75 GPM (2.84 LPM) @ 60psi
Maximum Working Pressure:	100 psig (689.5 kPa)
Minimum Working Pressure:	30 psig (206.8 kPa)
Maximum Operating Temperature:	100 °F (38 °C)
Minimum Operating Temperature:	34 °F (1 °C)

COLORS AVAILABLE



NOTICE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

** NSF Standard 53 Certification Pending.*

*** This water filtration device has not finalized certification with NSF International and has not been approved by the California Water Resource Control Board, therefore, it is not available for sale in the State of California for the contaminant reduction claims listed.*

Distributed by: