



IC/IS SERIES

Inline Filters

Hydro Guard™ IC/IS Series Inline Filters

Data Sheet

Hydro Guard™ HDGP IC/IS Inline Filters utilize NSF listed coconut shell GAC and are designed to remove unpleasant taste and odor and reduce sediment to produce cleaner, clearer, better tasting water. Hydroguard IC Series Granular Activated Carbon Filters are easily installed on the water line to an automatic ice maker, Reverse Osmosis System or water dispensing system.

- ✓ Superior spring design to minimize channeling
- ✓ 1/4", 3/8" Female NPT and quick connections
- ✓ Sediment and coconut shell carbon



Tested and certified by NSF International to ANSI/NSF Standard 42 for material requirements only.

2" DIAMETER SPECIFICATIONS						
	Part Number	Description	Case Quantity	Box Dimension (Inches)	Weight (lbs)	Weight (kgs)
6"	HDGP-IC-6	NSF Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" FNPT	50	12.5 x 11 x 11	18	8.16
	HDGP-IC-10	NSF Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" FNPT	25	10.5 x 10.5 x 11	17	7.71
10"	HDGP-IC-10Q	Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" QC	25	11.5 x 10.5 x 10.5	17	7.71
	HDGP-IS-10	Inline Sediment Filter: 2" x 10", 1/4" FNPT	25	10.5 x 10.5 x 11	12	5.44
	HDGP-IC-10KDF.5	Inline Coconut Filter: + .5 lbs KDF, 2" X 10", 1/4" FNPT	25	10.5 x 10.5 x 10.5	15	6.8
	HDGP-IC-CAL10Q	Inline 0.9 lbs Clack Calcite Filter: 2"X10", 1/4 QC	25	10.5 x 10.5 x 10.5	30	13.6
	HDGP-IC-CAL10Q38	Inline 0.9 lbs Clack Calcite Filter: 2"X10", 3/8 QC	25	10.5 x 10.5 x 10.5	30	13.6

2.5" DIAMETER SPECIFICATIONS						
	Part Number	Description	Case Quantity	Box Dimension (Inches)	Weight (lbs)	Weight (kgs)
12"	HDGP-IC-2512	NSF Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" FNPT	25	13.25 x 11.75 x 13.5	26	11.79
	HDGP-IC-2512Q	Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" QC	25	13 x 12.5 x 13.5	27	12.25
	HDGP-IS-2512	Inline Sediment Filter: 2.5" x 12", 1/4" FNPT	25	13.25 x 11.75 x 13.5	19	8.62
	HDGP-IS-2512Q	Inline Sediment Filter: 2.5" x 12", 1/4" QC	25	13.25 x 12.25 x 13.5	20	9.07
	HDGP-IS-2512Q-SR	Inline Scale Reduction Filter: 2.5" x 12", 1/4" QC	25	13.75 x 13.5 x 11.75	28	12.7

IC/IS SERIES

Inline Filters



HDGP-IC-10



HDGP-IS-10

Chlorine Taste & Odor Reduction - HDGP IC-10 | IC-10Q

Coconut Shell Carbon

Service Life	1 yr or 2000 gal (7570 L)
Maximum Flow	.50 gpm (1.9 lpm)
Maximum Pressure	125 psi (8.6 bar)
Maximum Temperature	100 °F (38 °C)
Minimum Temperature	35 °F (2 °C)

MATERIALS OF CONSTRUCTION

Shell:	Polypropylene
Media:	Coconut Shell Carbon
Inner Pads:	Polypropylene

AVAILABLE PORT SIZES

- 1/4" Female NPT Basic
- 3/8" Female NPT Basic
- 1/4" Quick Connect
- 3/8" Quick Connect

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Dirt & Sand Reduction - HDGP IS-10

Service Life:	Applications vary
Maximum Flow:	.50 gpm (1.9 lpm)
Maximum Pressure:	125 psi (8.6 bar)
Maximum Temp:	100 °F (38 °C)
Minimum Temp:	35 °F (2 °C)
Micron Rating:	5M

MATERIALS OF CONSTRUCTION

Shell:	Polypropylene
Media:	Polypropylene

APPLICATIONS

- Ice makers
- Reverse osmosis systems
- Water Coolers
- Coffee makers
- Refrigerators

LIT-HDGP-IC-HDGP-IS_DS 04/02/25



HYDRO GUARD™ WATER SCIENCES | PO Box 2235 Chino Hills, CA 91709, USA

Distributed By: