



P117 SERIES
Granular Activated Carbon Filter

Hydro Guard™ P117 Series Granular Activated Carbon Cartridges

Data Sheet

Hydro Guard™ P117 Series Cartridges

Are ideal for whole house pre filtration for the reduction of taste, odor, and chlorine. It's rigid construction eliminates sediment unloading and yield a low pressure drop. P117 filters are manufactured with FDA CFR-21 compliant materials and provide a flow rate of up to 3 gallons per minute for point-of-entry applications.

- ✓ Reduces bad taste, odor, and chlorine
- ✓ Dirt, rust and sediment reduction
- ✓ 5 micron sediment filtration



2.5" DIAMETER SPECIFICATIONS						
Part Number	Description	Case Quantity	Box Dimension (Inches)	Weight (lbs)	Weight (kgs)	
2.5" HDGP-P117	GAC Filter 2.5" x 9 3/4" 5 Micron	20	15.75 x 13 x 11	20.5	9.3	

**WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.*

MATERIALS OF CONSTRUCTION

Filter Media: Granular activated carbon
End Caps: Polystyrene
Core: Polypropylene

PRODUCT SPECIFICATIONS

Temperature Range: 40 °F to 125 °F (4.4 °C to 51.7 °C)
Flow Rate: 3 GPM



HYDRO GUARD™ WATER SCIENCES | PO Box 2155 Rancho Cucamonga, CA 91729, USA

Distributed By:

LIT-HDGP-P117_DS 09/25/25