



APPLICATIONS

- ✓ Ice Machines
- ✓ Food Service
- ✓ Drinking Water
- ✓ Beverages
- ✓ Sanitary Filter Cartridge

SPECIFICATIONS

Model:	HDG-7CB5-S
Alt. Model:	HDG-EV9218-21
Media:	Performance Carbon Block CB+ Scale Media 0.2m Cyst Barrier Media
Capacity:	10,000 Gallons (37,854 L)
Temperature:	35 °F – 100 °F (2 °C - 38 °C)
Max. Working Pressure:	125 psi (8.6 bar)
Pressure Requirement:	10 - 125 psi (0.7 – 8.6 bar)
Max. Service Flow Rate:	2.5 gpm (9.5 lpm)

HYDRO GUARD™ TRITEK MEDIA
WITH SCALE CONTROL



20.75" (52.7 cm)

HDG-7CB5-S

Carbon Block+ with Cyst Barrier Media
Scale Reduction Quick Change Cartridge

FEATURES • BENEFITS

Hydro Guard Water Sciences™ model HDG-7CB5-S sanitary filter cartridges utilize Tritex filtration media to effectively address Chlorine, Taste, Odor and dramatically improve aesthetics in drinking water. The HDG-7CB5-S cartridge addresses the growth of bacteria on the filter media and reduces scale buildup on equipment.

Hydro Guard™ HDG-7CB5-S are simple, quick and clean. The internal filter parts are never exposed to handling or contamination and offer true sanitary filter cartridge benefits for ease of use and optimal performance. The HDG-7CB5-S (also part number HDG-EV9218-21) cartridge reduces scale, chlorine taste and odor and other offensive contaminants that can adversely affect the taste of beverages. The TriTek filtration media for enhanced performance provides superior chlorine taste and odor reduction.

The **Hydro Guard™** HDG-7CB5-S sanitary filter cartridges micro-filter dirt and particles as small as 0.2 micron in size by mechanical filtration technology and comply with NSF/ANSI Standard 42 protocol.

Hydro Guard™ HDG-7CB5-S sanitary filter cartridges drastically improve the taste of ice, coffee and other beverages. They are ideal for commercial use and aid to keep equipment running at a more efficient capacity.

INSTALLATION TIPS OPERATION TIPS SIZING

- Always Install vertically with cartridge hanging down.
- Allow 2-1/2" (6.35 cm) clearance below the cartridge for easy cartridge replacement.
- Flush cartridge by running water through filter for five (5) minutes at full flow prior to use.

OPERATION TIPS

- Change cartridges on a regular six (6) month preventative maintenance program.
- Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).
- Always flush the filter cartridge at time of installation and cartridge change.

HDG-7CB5-S-DS 04/27/26

Distributed by:



HYDRO GUARD WATER SCIENCES | PO Box 2155 Rancho Cucamonga CA 91729, USA